

# Premium Care Oil



## 1 PRODUCT DESCRIPTION

Deeply effective care-oil based on vegetable oils and carnauba wax.

- Refreshes dull, especially heavily used and intensively cleaned oiled surfaces.
- Enhances the wood grain.
- Good penetration properties and high filling capacity.
- Satin-matt visual effect.

New recipe with higher solids content, lower odour and free of labelling obligation.

- Available as colourless or white.

## 2 SUITABLE FOR

For refreshing oxidative oiled wood and parquet floors, as well as oiled cork floors and oiled OSB, especially surfaces oiled with **Premium Hardwax Oil +**. Also suitable for industrially pre-oiled surfaces with high grain enhancement. In the case of UV-oiled surfaces we recommend testing beforehand. Not suitable for waterbased sealed surfaces without grain enhancement.

## 3 APPLICATION

Before application clean the floor well. Remove any care product layers by strip cleaning. Remove any stains before oiling and/or remove light scratches carefully with fine sandpaper.

Shake up well before use, take off a skin if one has formed. Apply Premium Care Oil onto the floor thinly and evenly with a fluff-free cloth. After allowing it to soak in for 15 minutes, polish out the oil film completely, removing any surplus. We recommend using a single disc machine (e.g. Dr. Schutz SRP1) with a white pad. After polishing the floor should have a uniformly satin-matt appearance.

In the case of serious damage of the surface to which the care product is applied, or when the absorbency of the parts in question is high, a further application may be necessary after the oil has dried.

Please note:

- Before using on exotic, coloured and unknown types of wood, check suitability by testing the product on a small area (at least 1 sq.m).
- On woods rich in resin, this can lead to the resin contained in the wood solvating and leaking, which may delay drying time, or result in irregularities in the appearance of the surface.
- Ensure adequate ventilation during application and drying, but avoid draughts or strong sunlight and protect the surface against dust. Switch off floor heating beforehand.

## 4 COVERAGE

50-100 m<sup>2</sup> (10-20 ml/m<sup>2</sup>), depending on absorbency of the floor

In the case of a highly absorbent subsurface increased consumption is possible, depending on its absorbency.

## Premium Care Oil



### 5 CURING

Can be walked on carefully and worked on again after approx. 6 hours (at 23 °C, 50% relative air humidity with ventilation). The surface should not be wet-mopped in the first 7 days. After 10 days at the earliest carpets can be laid on the floor.\*

Low temperatures, high humidity, poor ventilation and inhibiting substances contained in the wood can prolong the drying time substantially.

### 6 MAINTENANCE

### 7 STORAGE

Store in a cool, dry place in the closed original canister. Keeps for at least 24 months in unopened original canister from the date of manufacture. Keep locked up and out of the reach of children.

### 8 TECHNICAL DATA

Contains substances: vegetable oils, alkyd resin, carnauba wax, aliphatic hydrocarbons, drying agents free of lead and cobalt, additives.

ADR: not a dangerous good as defined by transport regulations.

CLP: no obligation to be labelled as hazardous.

GISCODE: Ö60

### 9 SPECIAL NOTES

- Warning! Danger of spontaneous combustion of working materials moistened with oil, e.g. cloths, pads, sanding dust, etc. Therefore allow working materials to dry openly spread out and only dispose of them when they are completely dried. Or soak them in water and shut them in an airtight metal container to dispose of them in a fire-safe way.
- Oiled surfaces smell. The odor fades over days in the course of increased drying. In the time directly after oil treatment ventilate the rooms well.
- Oiled surfaces typically manifest a yellowing tendency. This can lead to conspicuous areas, especially in the case of white pigmented sub-surfaces and variable light coverage.

### 10 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of Dr. Schutz finishes
- Safety data sheet available on request.

## Premium Care Oil



The quoted printed matter, as well as this product information in its updated form, is available on our homepage [www.dr-schutz.com](http://www.dr-schutz.com) or on request from the address quoted below.

### Dr. Schutz – We Care About Floors

Headquarter  
Dr. Schutz GmbH  
Holbeinstraße 17  
D-53175 Bonn  
Tel.: +49 (0)228 / 95 35 2-40  
Fax: +49 (0)228 / 95 35 2-46  
E-Mail: [export@dr-schutz.com](mailto:export@dr-schutz.com)  
[www.dr-schutz.com](http://www.dr-schutz.com)

UK  
Dr. Schutz U.K Ltd.  
Unit 24, Anglo Business Park,  
Smeaton Close, Aylesbury Bucks  
HP19 8UP

Contact: Richard Nelson  
Tel.: +44 (0)1296 437827  
Fax: +44 (0)1296 334219  
E-Mail: [richard@dr-schutz.com](mailto:richard@dr-schutz.com)

Ireland  
Dr. Schutz Ireland  
35 Pic Du Jer Park,  
Ballinlough, Cork

Contact: Paul O'Reardon  
Mobile: 0877678388  
E-Mail: [drschutzireland@gmail.com](mailto:drschutzireland@gmail.com)

North America  
Schutz NA  
4701 Bath St 46  
Philadelphia PA 19137  
USA

Contact: Sam Jamison  
Tel.: +1 (877) 272-4889  
Mobile: +1 (215) 510-7874  
E-Mail: [sam@schutzNA.com](mailto:sam@schutzNA.com)

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.